

Freeform Search

Database:	US Pre-Grant Publication Full-Text Database US Patents Full-Text Database US OCR Full-Text Database EPO Abstracts Database JPO Abstracts Database Derwent World Patents Index IBM Technical Disclosure Bulletins
Term:	(diode or transistor or junction) and (thermal or temperature) and (constant current) and (reference current) and (pads) and (integrated
Display:	<input type="text" value="10"/> Documents in Display Format: <input type="text" value="-"/> Starting with Number <input type="text" value="1"/>
Generate: <input type="radio"/> Hit List <input checked="" type="radio"/> Hit Count <input type="radio"/> Side by Side <input type="radio"/> Image	

Search History

DATE: Tuesday, October 03, 2006
 [Purge Queries](#)
 [Printable Copy](#)
 [Create Case](#)

<u>Set Name</u> side by side	<u>Query</u>	<u>Hit Count</u>	<u>Set Name</u> result set
	<i>DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=ADJ</i>		
<u>L23</u>	(diode or transistor or junction) and (thermal or temperature) and (constant current) and (reference current) and (pads) and (integrated circuit or IC or die or chip or CMOS)	241	<u>L23</u>
<u>L22</u>	(diode or transistor or junction) same (thermal or temperature) same (constant current) same (reference current) same (pads) and (IC or integrated circuit or die or chip)	1	<u>L22</u>
<u>L21</u>	L8 and (diode or transistor or junction) and (thermal or temperature) and (constant current) and (reference current) and (pads)	15	<u>L21</u>
<u>L20</u>	L8 and (diode or transistor or junction) same (thermal or temperature) same (constant current) same (reference current) and (pads)	1	<u>L20</u>
<u>L19</u>	L8 and (diode or transistor or junction) same (thermal or temperature) same (constant current) same (reference current) same (pads)	1	<u>L19</u>
	<i>DB=PGPB,USPT,USOC,EPAB,JPAB; PLUR=YES; OP=ADJ</i>		
<u>L18</u>	L17 and (pads)	55	<u>L18</u>
<u>L17</u>	L15 and (reference near current)	391	<u>L17</u>
<u>L16</u>	L15 and (reference near2 current)	592	<u>L16</u>

<u>L15</u>	(374/1,001,178,170,163;324/759-769;327/512,513;702/99,130)![CCLS]	14470	<u>L15</u>
<u>L14</u>	L11 and (reference near2 current)	117	<u>L14</u>
<u>L13</u>	L12 and (pads)	27	<u>L13</u>
<u>L12</u>	L11 and (reference current or bias current)	118	<u>L12</u>
<u>L11</u>	L10 and (constant current)	471	<u>L11</u>
<u>L10</u>	L8 and (IC or intergrated circuit or dye or die or chip)	5708	<u>L10</u>
<u>L9</u>	L8 and (IC or intergrated circuit or dye or chip)	5433	<u>L9</u>
<u>L8</u>	(374/178,170,163;324/759-769;327/512,513)![CCLS]	13064	<u>L8</u>
<i>DB=USPT; PLUR=YES; OP=ADJ</i>			
<u>L7</u>	5401099.pn.	1	<u>L7</u>
<u>L6</u>	6890097.pn.	1	<u>L6</u>
<u>L5</u>	5195827.pn.	1	<u>L5</u>
<u>L4</u>	6453218.pn.	1	<u>L4</u>
<u>L3</u>	6554469.pn.	1	<u>L3</u>
<u>L2</u>	6554469.pn.	1	<u>L2</u>
<u>L1</u>	5639163.pn.	1	<u>L1</u>

END OF SEARCH HISTORY